



MAIN SPECS



CAPACITIES

Payload Distributed Capacity
Tie-down Load Rating
Bearing Load Rating

Load
 Carrier
 Side-Thrust

Plus-Nut Rating (1/8" steel)
Extension

1200 lbs
400 lbs per tie-down
Combined Load Rating
of Bearings = 18,864
 2 @ 4840 ea.
 2 @ 3019 ea.
 2 @ 1573 ea.
 4 - 6 @ 1500 lbs. each
 65-75%

DIMENSIONS / WEIGHT RANGES

Length
Width
Profile/ Deck Height (inches)
Side Rails
Grab Rail
Weight

36" - 95"
 22" - 48"
 4 1/2"
 4"
Based on width of unit
 110 - 210 lbs

1200 lb capacity. 75% of the Cargo Tray Length Slides Out on short bed trucks and 65% on long beds. Sturdy steel frame construction. Real plywood deck with a TPO rubber laminated surface for strength and durability. 6 Industrial Cam Follower Needle and Ball Bearings provide Dependable Lasting support for the Cargo You Haul in Your CargoGlide. Industrial 4" high extruded 6061-T6 Thick Aluminum Side Rails with integrated Full Perimeter Tie-Down Tracks and Four Infinitely Adjustable Eyebolt Tie-Downs to make securing cargo easy and versatile.

Custom Sizes Available

