



## MAIN SPECS



## CAPACITIES

**Payload Distributed Capacity**  
**Tie-down Load Rating**  
**Bearing Load Rating**

Load  
 Carrier  
 Side-Thrust

**Plus-Nut Rating (1/8" steel)**  
**Extension**

**1500 lbs**  
**400 lbs per tie-down**  
**Combined Load Rating**  
**of Bearings = 18,864**  
 2 @ 4840 ea.  
 2 @ 3019 ea.  
 2 @ 1573 ea.  
 4 - 6 @ 1500 lbs. each  
 65 - 75%

## DIMENSIONS / WEIGHT RANGES

**Length**  
**Width**  
**Profile/ Deck Height (inches)**  
**Side Rails**  
**Grab Rail**  
**Weight**

36" - 95"  
 22" - 48"  
 4 1/2"  
 4"  
**Based on width of unit**  
 110 - 210 lbs

**1500 lb capacity.** 75% of the Cargo Tray Length Slides Out on short bed trucks and 65% on long beds. Sturdy steel frame construction. Real plywood deck with a TPO rubber laminated surface for strength and durability. 6 Industrial Cam Follower Needle and Ball Bearings provide Dependable Lasting support for the Cargo You Haul in Your CargoGlide. Industrial 4" high extruded 6061-T6 Thick Aluminum Side Rails with integrated Full Perimeter Tie-Down Tracks and Four Infinitely Adjustable Eyebolt Tie-Downs to make securing cargo easy and versatile.

**Custom Sizes Available**

