



MAIN SPECS



CAPACITIES

Payload Distributed Capacity
Tie-down Load Rating
Bearing Load Rating

Load
 Carrier
 Side-Thrust

Plus-Nut Rating (1/8" steel)
Extension

1800 lbs
400 lbs per tie-down
Combined Load Rating
of Bearings = 18,864
 2 @ 4840 ea.
 2 @ 3019 ea.
 2 @ 1573 ea.
 4 - 6 @ 1500 lbs. each
 65 - 75%

DIMENSIONS / WEIGHT RANGES

Length
Width
Profile/ Deck Height (inches)
Side Rails
Grab Rail
Weight

36" - 95"
 22" - 48"
 4 3/4"
 4" with 8" High Sides
 Based on width of unit
 155 - 251 lbs

1800 lb capacity. 75% of the Cargo Tray Length Slides Out on short bed trucks and 65% on long beds. Real plywood deck with a TPO rubber laminated surface for strength and durability. 6 Industrial Cam Follower Needle and Ball Bearings provide Dependable Lasting support for the Cargo You Haul in Your CargoGlide. Industrial 4" high extruded 6061-T6 Thick Aluminum Side Rails with integrated Full Perimeter Tie-Down Tracks and 4 Infinitely Adjustable Eyebolt Tie-Downs to make securing cargo easy and versatile. Includes 8" High Side Extensions on the first four feet of the rails at the cab end, helps contain more cargo.

Custom Sizes Available

